



PRODUCT TECHNICAL DATA SHEET

Underfloor Closed®

PRISMI[®]
rubber powder

The EU pioneer supplier of Rubber Granules poured in place since 1990

COMMERCIAL NAME:	UNDERFLOOR CLOSED
SIZE:	1-4 mm
ID CORE RUBBER GRANULES:	<u>RUBBER SECONDARY RAW MATERIAL</u>
SURFACE:	COLORFUL
COLOR:	BLACK



PHYSICAL PROPERTIES

Rubber Material		SBR/NR
Transport Bulk Density		0,57 (+/- 0,3)
Uncompacted Bulk Density		0,47 (+/- 5%)
Absolut Density		1,15 (+/- 5%)
Type		100% Vulcanized Rubber to majority Truck Tyre
Hardness		60<>64 shore A
Moistness		0,5%
No Rubber Particles		0,01 % in weight
Dimensional	Lab Equipment	RETSCH EasySieve AS200 Screens: Test Sieve ISO3310-1
	Granulometry	Nominal size 1.0 mm to 4 mm
	Testing	Periodic granulometric analysis according to EN933-1 standard
Quantity x sqm thickness 10 mm		5 KG (+/- 10%)

HIC (mt)	THICKNESS/SQM (mm) +10 mm TOP	RUBBER QUANTITY (KG)	ISOCYANATE QUANTITY (KG)
1,2	35	21	>1,89
1,5	50	30	>2,7
1,8	60	36	>3,24
2,1	70	42	>3,78
2,5	80	48	>4,32
3,0	100	60	>5,4

This information is indicative and Prismi srl **is not responsible** for the final result. The surface, the type of binder and the method of laying, influence the result even by 0.5 meters

